



Please use this reference chart for USB video support

Container	Video Codec	Audio Codec	Resolution
AVI(.avi/.divx)	MP4V DIVX3.xx/4.xx/5.xx /6.xx Xvid MPEG-1 MSVC	Dolby Digital(AC3) WMA/PCM/LPCM AAC LC (2ch) MPEG-Audio (MP1/MP2/MP3)	720*480/576 (30fps)
MPG(.mpg/.mpeg)	MPEG-1/MPEG-2	Dolby Digital(AC3) LPCM MPEG-Audio	720*480/576 (30fps)
DAT(.dat)	MPEG-1/MPEG-2	Dolby Digital(AC3) LPCM MPEG-Audio	720*480/576 (30fps)
FLV(.flv)	H.263	LPCM/MP3	720*480/576(30fps)
RMVB(.rm/.rmvb/.rmv/ra)	RV8/9/10	COOK AAC LC (2ch)	1280*720 (30fps)
VOB(.vob)	MPEG-1/MPEG-2	Dolby Digital(AC3)	720*480/576 (30fps)
MP4/MOV(.mp4/.mov/.xvid)	DIVX3.xx/4.xx/5.xx /6.xx Xvid MP4V	Dolby Digital(AC3) WMA/LPCM AAC LC (2ch) MPEG-Audio (MP1/MP2/MP3) uLaw/aLaw	720*480/576 (30fps)
ASF(.asf)		WMA	WMAOnly Support, including: WMA7、WMA8、WMA9 (CBR、 VBR) (Only Support 353) Sampling Rate :8K~48KHz. Bitrate : 16kbps~320kbps.

Document Illustrated and Approved By: Robert Rucker
Date: 3/2/17
Technical Support
Alpine Electronics of America, Inc.
1-800-TECH-101

Additional Specifications:
N/A

Circuit Profile:
N/A

Revision: 012915 This document will be subjected to change without notice.